

Sartopure GF2

Adsorptive High Capacity Filter Capsules and MaxiCaps



Description

Sartopure GF2 capsules are optimized for the protection of downstream membrane filter systems and clarification in biopharmaceutical production processes. Due to their high adsorptive power by glass fiber fleeces, Sartopure GF2 filters are the ideal solution for removal of colloids and lipids from biopharmaceutical fluids.

Applications

Sartopure GF2 are ideal for the prefiltration of:

- Fermentation Broths
- Cell Debris solutions
- Serum
- Plasma
- LVP
- Colloid containing solutions
- Lipid containing solutions

High Adsorption

Based on electrostatic forces of attraction, the negatively charged glass fiber filter material of Sartopure GF2 retains positively charged, small particles that would otherwise pass through the filter.

Defined Retention Rates

One of the key features of Sartopure GF2 cartridges is their defined and accurate retention rating of >99.9%!

High Profitability

Other key attributes of Sartopure GF2 filters – high flow rates at low differential pressures and high total throughput – guarantee the maximum in reduced cost and process efficiency.

Flexibility

Sartopure GF2 filters are available in various sizes as Maxicaps, capsules, standard filter cartridges and mini-cartridges to allow for broadest choice and highest process flexibility.

Documentation

Sartopure GF2 cartridges are designed, developed and manufactured in accordance with a ISO 9001 certified Quality Management System. A Validation Guide is available for compliance with regulatory requirements.

Specifications

Materials

Filter Material:	Glass Fiber Fleeces
Support fleece:	Polypropylene
Core:	Polypropylene
End caps:	Polypropylene
Outer shell:	Polypropylene

Retention Rates

0.65 µm, 1.2 µm, 3 µm

Available Sizes | Filtration Area

MaxiCaps

Size 1	10"	0.6 m ²	6 ft ²
Size 2	20"	1.2 m ²	12 ft ²
Size 3	30"	1.8 m ²	18 ft ²

Capsules

Size 7	0.05 m ²	0.5 ft ²
Size 8	0.1 m ²	1 ft ²
Size 9	0.2 m ²	2 ft ²
Size 0	0.45 m ²	5 ft ²

Available Connectors

SS, 00, S0

Operating Parameters

Max. Allowable	4 bar	58 psi at 20 °C
Differential Pressure:	2 bar	29 psi at 80 °C

Max. Allowable Back Pressure:	2 bar	29 psi at 20 °C
-------------------------------	-------	-----------------

Depth Filter Capsules

Specifications

Extractables

Sartopure GF2 capsules meet or exceed the requirements for WFI quality standards set by the current USP.

Regulatory Compliance

Non pyrogenic according to USP Bacterial Endotoxins

Pass USP Plastic Class VI Test

Non fiber releasing according to 21 CFR

Sterilization

Autoclaving

134 °C, 2 bar | 29 psi, 30 min

Sterilization Cycles


Min. 25

Technical References

Validation Guide:


SPK 5717-e

Water Flow Rates for Sartopure GF2 10" Standard Cartridges 0.65 µm, 1.2 µm, 3 µm + MaxiCaps (0.65 µm, 1.2 µm)



Standardized at 20 °C

Ordering Guide:



Sartorius AG
Weender Landstrasse 94-108
37075 Goettingen, Germany
Phone +49.551.308.0
Fax +49.551.308.3289
www.sartorius.com

USA +1.631.2544249
UK +44.1372.737100
France +33.1.69192100
Italy +39.055.634041
Spain +34.91.3586100
Japan +81.3.33293366

Specifications subject to change without notice.
Printed and copyrighted by Sartorius · W/sart-000 · G
Publication No.: S--2025-am04051
Order No.: 85030-520-17